APPLICATION

FOR

UNITED STATES LETTERS PATENT

TITLE: DIRECT ELECTRICAL-TO-OPTICAL CONVERSION AND LIGHT MODULATION IN MICRO WHISPERING-GALLERY-MODE RESONATORS

APPLICANT: LUTFOLLAH MALEKI AND ANTHONY F.J. LEVI

DIRECT ELECTRICAL-TO-OPTICAL CONVERSION AND LIGHT MODULATION IN MICRO WHISPERING-GALLERY-MODE RESONATORS

This application claims the benefit of U.S. Provisional

5   Application No. 60/212,091 filed on June 15, 2000.

Origin of the Invention

The systems and techniques described herein were made in

the performance of work under a NASA contract, and are subject

10   to the provisions of Public Law 96-517 (35 USC 202) in which the

Contractor has elected to retain title.

Background

This application relates to conversion from an electrical

15   signal to an optical signal and light modulation in response to

an electrical signal.

An electrical signal may carry certain information in

either digital or analog form. The information can be imbedded

in a property of the electrical signal such as the phase or the

20   amplitude. The information in the electrical signal may be

created in various ways, e.g., by artificially modulating the

electrical carrier, or by exposing the electrical carrier to a

medium which interacts with the carrier. In some applications,

such information may be transmitted, processed, stored,

25   received, or detected in the electrical domain. For example,

electrical cables can be used to transmit information in

electrical form; many electronic circuits or processors (e.g.,

microprocessors) can process information in electrical form;

satellites, radars, and wireless telephones or other electronic

devices can transmit or receive information in electromagnetic

5   waves traveling in free space without relying on conductive

transmission media.

An optical wave may also be used as a carrier to carry

information in either digital or analog form. Similar to an

electrical signal, an optical carrier wave may be artificially

10   modulated to carry desired information, or may be brought into

interaction with an optical medium to acquire certain

information indicating a characteristic of that medium.

Examples for the artificial optical modulation include optical

modulation by using an optical modulator such as an electro-

15   optic material whose refractive index changes with an applied

electric field, or modulation of a driving current in a

semiconductor gain material (e.g., a multiple-quantum-well gain

medium) which amplifies or generates an optical wave. Examples

for interaction between an optical wave and an optical medium

20   include measurements of the optical scattering, reflection, or

transmission of optical media. Also similar to electrical

signals, optical signals may be transmitted in free space or in

optical transmission media such as optical waveguides (e.g.,

optical fibers or planar waveguides formed on semiconductor,

glass or other substrates). In addition, optical signals may be processed or manipulated optically by using optical devices and stored in optical storage media.

Signal transmission, processing, or storage in optical domain may have advantages over the electrical counterpart in certain aspects. For example, optical signals are generally immune to electromagnetic interference which often limits the performance of electronic devices. Also, an optical carrier, having a carrier frequency much higher than that of an electrical signal, can carry more information than an electrical carrier due to the wider bandwidth associated with the higher optical carrier frequency. As another example, optical signals can be used allow for easy parallel transmission and processing to further increase the information carrying capacity as well demonstrated by the optical wavelength-division multiplexing (WDM) techniques.

Many applications may be designed to have electrical-optical "hybrid" configurations where both optical and electrical signals are used to explore their respective performance advantages, conveniences, or practical features. Some existing communication systems, for example, transmit signals in the optical form through fiber networks but process the information at a destination in electronic form (e.g., by

one or more digital electronic processors). In such and other

applications, the electrical-to-optical conversion is needed.

Summary

5   This disclosure includes techniques for directly converting

an electrical signal to an optical signal by using a micro

whispering-gallery-mode resonator. The resonator may be formed

of a dielectric material that has at least three different

energy levels to allow for (1) at least one optical transition

10   between the first and second energy levels at the signal

wavelength of the optical signal and (2) an electronic

transition between the second and third energy levels in

resonance with the frequency of the electrical signal. In

absence of the electronic transition between the second and the

15   third energy levels caused by the electrical signal, the

electronic population for optical transition between the first

and second energy levels is optically transferred to the third

energy level and hence no optical absorption occurs due to the

population depletion. As a result, the dielectric material is

20   optically transparent to the optical signal at the signal

wavelength. When the resonator is exposed to the electrical

signal oscillating at the resonance frequency between the second

and third energy levels, the electrons trapped in the third

energy level are transferred to the second energy level and

hence become available for optical absorption so that the dielectric material is optically absorptive at the signal wavelength.

This direct interaction between the electrons and the applied electrical signal is used to modulate the optical absorption of the dielectric material. Since the quality factor of the resonator varies with the optical absorption of the dielectric material, a change in the electrical signal, such as the frequency or the amplitude, can modulate the quality factor by changing the optical absorption of the dielectric material to cause an optical modulation on the optical signal in the resonator. This operation directly converts the modulation in the electrical signal into a modulation in the optical signal.

The whispering-gallery-mode design of the resonator is used to provide an efficient coupling environment between the electrical modulation and the optical modulation. In absence of the electrical signal, the whispering-gallery-mode resonator, when properly designed, can achieve a high quality factor, which in turn produces narrow spectral linewidth of a supported whispering gallery mode. The electronic modulation by the electrical signal in resonance with the second and third energy levels causes the resonator to operate between the high quality factor and a low quality factor. Since the optical energy confined in a whispering gallery mode of the resonator is highly

sensitive to the quality factor, a small amount of absorption of the electrical signal to cause an electronic population transfer from the third "trapped" energy level to the second energy level can be effectively amplified in an optical modulation on the

5   amount energy stored in the resonator.

This system hence can provide not only an efficient electrical-to-optical conversion but also a highly sensitive detection method for measuring the electrical signal. In principal, a single event of absorption of a photon in the

10   electrical signal by the dielectric material can be optically measured in this system. Various devices and systems may be built based on this whispering gallery mode resonator for electrical-to-optical conversion, optical modulation, and optical sensing of electrical signals.

15

Brief Description of the Drawings

FIG. 1 shows one embodiment of a direct electrical-to-optical conversion system based on a micro whispering-gallery-mode resonator formed of a dielectric material with appropriate

20   energy levels for interaction with an input electrical signal and an input optical signal.

FIGS. 2A and 2B show exemplary implementations of the evanescent coupler in FIG. 1.

FIGS. 3, 4, 5, 6, and 7 show exemplary implementations of the electrical coupler in FIG. 1 for applying the input electrical signal to a portion or the entirety of the resonator.

FIG. 8 shows one embodiment of the desired energy level structure in the dielectric material used for the resonator in FIG. 1, which has an excited state and two ground states.

FIG. 9 shows the relevant energy levels in Chromium-doped ruby as one exemplary implementation of the dielectric material with the energy structure shown in FIG. 8.

Detailed Description

FIG. 1 shows one embodiment 100 of a direct electrical-to-optical conversion system based on a micro whispering-gallery-mode resonator 101 formed of a dielectric material with

5 appropriate energy levels. In one implementation, the micro resonator 101 generally may be formed from at least a portion of a whole dielectric sphere that includes the equator of the sphere. Such a resonator can support a special set of resonator modes known as "whispering gallery modes" which are essentially

10 electromagnetic field modes confined in an interior region close to the surface of the sphere around its equator and circulating by total internal reflection inside the axially symmetric dielectric body. Microspheres with diameters on the order of $10\sim10^2$ microns have been used to form compact optical resonators.

15 Such resonators have a resonator dimension much larger than the wavelength of light so that the optical loss due to the finite curvature of the resonators can be small. The primary sources for optical loss include optical absorption in the dielectric material and optical scattering due to the inhomogeneity of the

20 sphere (e.g., irregularities on the sphere surface). As a result, a high quality factor, Q, may be achieved in such resonators. Some microspheres with sub-millimeter dimensions have been demonstrated to exhibit very high quality factors for light waves, exceeding 109 for quartz microspheres. Hence,

optical energy, once coupled into a whispering gallery mode, can circulate at or near the sphere equator with a long photon life time. The resonator 101 may be the whole sphere or a portion of the sphere near the equator that is sufficiently large to

5   support the whispering gallery modes such as rings, disks and other geometries.

The micro resonator 101 may also have non-spherical resonator geometries that are axially symmetric. Such a non-spherical resonator may be designed to retain the two-

10   dimensional curvature confinement, low scattering loss, and very high Q values of typical spherical resonators (spheres, disks, rings, etc.). In one embodiment, instead of minimizing the eccentricity, such a non-spherical resonator may be formed by distorting a sphere to a non-spherical geometry to purposely

15   achieve a large eccentricity, e.g., greater than 10^{-1}. U.S. Application entitled "NON-SPHERICAL WHISPERING-GALLERY-MODE MICROCAVITY" and filed March 22, 2001 by Maleki et al., for example, describes an oblate spheroidal microcavity or microtorus formed by revolving an ellipse around a symmetric

20   axis along the short elliptical axis.

In both spherical and non-spherical micro resonators, optical energy can be coupled into the resonator by evanescent coupling, e.g., using an optical coupler 110 near the resonator 101 by less than one wavelength of the optical radiation to be

coupled. Although a whispering gallery mode confined within the resonator 101, its evanescent field 112 "leaks" outside the resonator 101 within a distance about one wavelength of the optical signal 114. The optical coupler 110 may have a

5   receiving terminal to receive an input optical wave 114 at a selected wavelength and a coupling terminal to evanescently couple the optical wave 114 into the resonator 101. In addition, the optical coupler 110 may also be used to couple the optical energy in one or more whispering gallery modes out of

10   the resonator 101 to produce an optical output 116. The output 116 may be coupled to an optical detector to convert the information into electronic form or an optical device or system for photonic processing, optical storage, or optical transmission such as a fiber link. The input optical beam 114

15   may be generated from a light source 120 such as a laser.

In one embodiment, the evanescent coupler 110 may be implemented by using one or two angle-polished fibers or waveguides 110A and 110B as shown in FIG. 2A. The angle-polished tip is placed near the resonator 101 to effectuate the

20   evanescent coupling. The index of refraction of the fibers or waveguides 110A and 110B is greater than that of the resonator 101, and the optimal angle of the polish has to be chosen depending on the ratio of indices. See, e.g., V.S. Ilchenko, X.S. Yao, L. Maleki, Optics Letters, Vol.24, 723(1999). In

another embodiment, evanescent coupler 110 may be implemented by

using one or two micro prisms 110C and 110D as shown in FIG. 2B.

A single angle-polished waveguide or fiber, or a single micro

prism may be used to operate as the evanescent coupler 110 to

5   couple both the input wave 114 and the output wave 116.

An electrical coupler 130 is provided in the system 100 to

supply an electrical signal 132 at a selected electrical

frequency in the RF, microwave, or millimeter spectral ranges

for interaction with the selected energy levels of the

10   dielectric material of the resonator 101. The electrical

coupler 130 may be in various configurations to couple the

electrical signal 132 to at least the region of the resonator

101 where the whispering gallery modes are present. The

electrical signal 132 may be received from a unit 140 which may

15   be an electrical signal generator, an antenna, a signal

transmitter, or a material exposed to an electromagnetic

radiation. When the signal 132 is generated by a signal

generator 140, desired data or other information may be used to

modulate the signal 132.

20   FIG. 3 shows one implementation 300 enclosed in a device

housing 380 based on the system 100 in FIG. 1. Optical fibers

332 and 334 are used to guide input and output optical beams.

Microlenses 331 and 333, such as gradient index lenses, are used

to couple optical beams in and out of the fibers 334 and 332.

Two prisms 321 and 322 are used as the evanescent couplers to

provide evanescent coupling with a whispering gallery mode

resonator 310. A RF microstrip line electrode 350 is used as

the electrical coupler and is engaged to the resonator 310 to

5 form a RF resonator to supply the electrical signal in

electrical modes that are localized in the region where the

optical whispering gallery modes are present. An input RF

coupler 330 formed from a microstrip line is implemented to

input the electrical energy into the RF resonator. A circuit

10 board 360 is used to support the microstrip lines and other RF

circuit elements. A second RF coupler 370, which may be formed

from a microstrip line on the board 360, may also be used to

produce a RF output. This signal can be used as a monitor for

the operation of the device 300 or as an electrical output for

15 further processing or driving other components.

FIGS. 4, 5, and 6 show examples of the microstrip line

electrode 350 when the resonator 310 is a disk or a ring that

includes a partial sphere with the equator. In FIG. 4, the

electrode 350 is formed on the top surface of the resonator 310

20 and another electrode 410 is formed in contact with the bottom

surface of the resonator 310. FIG. 5 shows a half-circuit

microstrip line as the top electrode 350 on the rim of the top

surface. FIG. 6 shows two pieces of circular microstrip lines

350A and 350B (solid lines) as the top electrode 350 and two

pieces of circular microstrip lines 410A and 410B as bottom

electrodes (dot liens with shades).

Alternatively, the electrical coupler 130 in the system 100

of FIG. 1 may be designed to apply the electrical signal 132 to

5   the entire resonator 101. FIG. 7 shows that a microwave

resonator 700 may be used to enclose the optical micro resonator

101 and to fill the entire resonator 101 with the electrical

signal 132. An opening is formed in the microwave resonator 700

to receive the electrical signal 132 so that the electrical

10   energy from the electrical signal 132 is stored in one or more

microwave modes of the resonator 700.

Notably, the dielectric material for the micro resonator

101 is specially designed or selected to have an energy

structure shown in FIG. 8 for interacting with both the input

15   electrical signal 132 and the input optical signal 114. The

energy structure has three energy levels 801a, 801b, and 801c

where 801a and 801c are two different ground states and the

level 801b is an exited state. Optical transitions are

permissible from both ground states 801a and 801c to the excited

20   state 801b. For example, upon absorbing an photon from the

input optical signal 114 in resonance with the transition 810

from the ground state 801a to the excited state 801b, an

electron is excited from the ground state 801a to the excited

state 801b. This electron on the excited state 801b, in turn,

can emit an photon and thus decay to either of the ground

states, generally with different delay rates. Arrowed lines 820

and 830 represent such radiative delay processes. The two

ground states have an energy difference 840 that corresponds to

5   a frequency in the electrical domain, e.g., the RF, microwave,

and millimeter spectral ranges. In addition, the relaxation or

decay rate from the upper ground state 801a to the lower ground

state 801c is small and is practically negligible in comparison

with the delay rates from the excited state 801b to either

10   ground state.

The above energy structure provides an optical pumping

scheme to allow for direct conversion of the electrical signal

132 in resonance with the energy gap 840 to the optical signal

114 with a frequency in resonance with either of the optical

15   transitions from the ground states 810a and 801c to the excited

state 801b. Assume, for example, no electrical signal is

applied to cause relaxation or redistribution of the electron

population between the two grounds states 801a and 801c and

there is an initial electron population in the ground state

20   801a. Also assume the optical signal 114 is in resonance with

the transition 810 so that electrons on the ground state 801a

absorb light in the optical signal 114 to jump to the excited

state 801b while the electrons on the other ground state 801c do

not absorb light and remain there. Once on the excited state

801b, a portion of the electrons emit photons at a wavelength in resonance with the transition 830 and decay to the other ground state 801c which is not optically excited. The remaining excited electrons decay back to the original ground state 801a

5   and absorb light again. The net result of the above cycle is that, a portion of the electrons originally in the ground state 801a are transferred to the other ground state 801c. In absence of optical excitation, these electrons will remain at the ground state 801c. That is, the electron population available for

10 optical absorption for the optical transition 810 is depleted. After a few cycles, no electrons will be left on the ground state 801a for the optical transition 810 and all electrons are transferred to and "trapped" in the other ground state 801c. As a result, the dielectric material of the resonator 101

15 essentially becomes completely transparent to the optical signal 132.

One consequence of this complete transparency state of the dielectric material is the optical loss is at the minimum. Therefore, the quality factor Q of the resonator 101 reaches its

20 maximum if the optical signal 114 is coupled into the resonator 101 by the evanescent coupler 110 in a mode matched condition. This maximum Q can be high because whispering gallery mode micro resonators are known for high Q values. In general, the quality factor Q is limited by the attenuation of radiation in the

dielectric material and the surface imhomogeneities. Some

microspheres have been shown to have very high quality factors

for light waves, exceeding 10^9 for quartz microspheres. See,

e.g., Braginsky V.B., Gorodetsky M.L., Ilchenko V.S, Phys.Lett.,

5 Vol.137, p.393(1989) and Collot et al., Europhys. Lett., Vol.

23, p.327(1993). Such high Q values may allow concentration of

strong fields in the whispering gallery modes. In quartz

spheres of diameter on the order of 100 microns, whispering

gallery modes may propagate very close to the surface of the

10 resonator, typically in a thickness less than 10 microns. High.

Q values can also be achieved for waves in the mm and microwave

regions of the electromagnetic spectrum.

The use of the dielectric material with the energy

structure of FIG. 8 also suggests that, the quality factor Q of

15 the resonator 101 is a sensitive function of the optical

absorption. As the optical absorption changes, the optical

energy confined in the resonator and hence optical output 116

change accordingly. This can be used to directly convert the

modulation in the electrical signal 132 in resonance with energy

20 gap 840 between the ground states 810a and 801c into modulation

in the output optical signal 116. The following explains the

basic operation of this scheme.

As described above, in absence of the electrical signal

132, the optical transition 810 between the ground state 801a

and the excited state 801b transfers all electron population

initially in the ground state 801a to the other ground state

801c which no longer interact with the optical signal 132. If

the electrical signal 132 is at a frequency in resonance with

5   the energy gap 840, the photons in the electrical signal 132 are

absorbed by the electrons trapped in the ground state 801c to

jump to the depleted ground state 801a. This process in effect

makes the electrons available for absorbing energy in the

optical signal 132 under transition 810 to artificially overcome

10 the lack of sufficient relaxation between the ground states 801a

and 801c. In addition, the quality factor Q of the resonator

101 is significantly reduced due to the increase of the optical

loss. Therefore, the dielectric material becomes at least

partially opaque to the optical signal 114. The degree of this

15 opaqueness of the dielectric material depends on the

characteristics of the signal 132, such as the deviation of the

frequency of the signal 132 from the resonance frequency of the

energy gap 840, the amplitude of the signal 132, or both the

frequency deviation and the amplitude. This dependence can be

20 used to directly convert a modulation in the electrical signal

132 to the optical signal in the resonator 101 or the output

optical signal 116.

For example, the frequency of the electrical signal 132 may

be modulated to be on and off the resonance condition to turn on

or off the repopulation between the ground states 801a and 801c

to modulate light in the whispering gallery mode. Also, the

intensity or power of the electrical signal 132 may be modulated

to change the strength of the repopulation to modulate the

5   light.

The dielectric material with the energy structure in FIG. 8

may be implemented by using a range of materials. Certain

crystals or glass materials may be doped. Chromium-doped ruby,

for example, may be used. FIG. 9 shows the relevant energy

10   states of Chromium ions in ruby where the hyperfine splitting of

the ground state $^4A_2$ produces two ground states $^4A_2(1/2)$ and

$^4A_2(3/2)$ that are separated by about 11.5 GHz. The transition

from the ground state $^4A_2$ to the excited state E is the "R_1"

transition at a wavelength of about 694.3 nm. A micro sphere

15   resonator formed of such doped ruby with a diameter of 2.5 mm is

estimated to produce an intrinsic quality factor of about 10^8.

The estimated Q may be about 10,000 at the room temperature.

In practice, the microwave at 11.5 GHz may be coupled to

fill the entire resonator. This can be advantageous because the

20   optical field in the whispering gallery mode, confined to a

small mode volume of less than about 30-micron radial extent

near the equator surface, partially overlaps the microwave

field. This partial overlap allows for the use of ruby with

normal concentrations of chromium ions to reduce the effect of

relaxation between the hyperfine ground states. The rate of

this relaxation is ordinarily high so that absorption may be

observed at a temperature of about 77 K or below. The Cr^{3+}

concentration should be small so that the relaxation process

5   does not mask the absorption of the applied microwave field.

The signal generated through relaxation (i.e., noise) should be

smaller than the applied microwave power (signal). At the room

temperature, the relaxation rate between the two ground states

$^4A_2(1/2)$ and $^4A_2(3/2)$ is about 10^7 per second. Hence, for a ruby

10   sphere of 2.5 mm and doped with chromium at 1.2×10^{18} per cubic

centimeter, the microwave power for this relaxation rate is

about 0.1 microwatts. This noise is about a factor of 10 less

than the goal of detecting a signal of one microwatt. Thus, the

partial and incomplete overlap between the optical mode and a

15   portion of the microwave field volume in fact can facilitate the

detectability of this signal level above the noise. The above

estimate is approximate in that the loss in coupling the

microwave power to the resonator is not included.

Chromium is just one example of various suitable dopants

20   for the dielectric material for the resonator 101. Notably,

other transition elements, such as the magnetic ions like

manganese or iron, may also be used to dope ruby or other

dielectric materials. Different ions generally have different

hyperfine splitting of the ground state so that different

electrical frequency ranges may be achieved.   For a given

dopant ion, the Zeeman splitting of the ground-state hyperfine

lines may be controlled by applying and controlling an external

magnetic field.   As the magnitude of the applied external

5   magnetic field is adjusted, the operating frequency range of the

electrical signal 132 can be adjusted accordingly to match the

changed energy gap 840.   In addition, the Zeeman splitting may

be controlled internally by using proper dopants that affect the

net magnetic field at the sites of the active ions.   The two

10   techniques for controlling the Zeeman splitting of the active

ions may also be combined.   The use of the external magnetic

field can provide a tuning capability to the system 100 by

adjusting the magnetic field.

Hence, the present scheme works based on the direct

15   absorption of the electrical signal 132 by the electrons in the

dielectric material.   This process directly changes the electron

population available for participating the optical transition in

resonance with the input optical signal 114 coupled into the

whispering gallery mode of the resonator 101.   In this context,

20   the electrical to optical conversion is direct and can be highly

efficient to allow for single microwave photon detection of an

electrical signal or sensitive and efficient electrical-to-

optical conversion.

The system 100 in FIG. 1 may be used as a highly sensitive

wireless RF or microwave receiver or transceiver. An antenna

may be used to receive the signal 132 and supply the received

signal 132 to the electrical coupler 130. When a received

5   signal 132 matches the energy gap 840 of the ground states 801a

and 801c, the information in the signal 132 is converted into

the optical domain in the optical output 116. The high Q factor

of the resonator 101 effectuates an amplification of the

modulation in the received electrical signal upon conversion

10   into the optical modulation. The higher the Q, the greater this

amplification. Therefore, the system 100 may be used for

receiving signals in a wireless network of RF transceivers such

as in a base station or a moving transceiver in a wireless

communication network or in a satellite communication system.

15   This system 100 can also detect electromagnetic radiation

emitted from a medium or sample under measurement. The measured

modulation can be extracted to determine certain properties,

such as the molecular or atomic structure of the sample.

In addition, the system 100 may be used as a highly

20   efficient and low power optical modulator for a range of

applications, including optical transmitter or transceiver in an

optical communication systems or as an communication interface

between an electronic wireless or wired communication system and

an optical free-space or fiber communication system.

It is further contemplated that, the above direct electrical-to-optical conversion mechanism may be combined with electro-optic modulation techniques. In addition to the energy structure shown in FIG. 8, the dielectric material of the

5 resonator 101 may also be designed to exhibit the electro-optic effect so that its refractive index changes with an applied electrical field. U.S. Application No. 09/591,866 filed on June 12, 2000 by Maleki et al., for example, describes electro-optic modulators based on micro whispering gallery mode resonators.

10 This combination can be used to form novel modulators.

Only a few embodiments are disclosed. However, it is understood that variations and enhancements may be made without departing from the spirit of and are intended to be encompassed by the following claims.